

Ultrapac Renovate

1	PRODUCT AND COMPANY IDENTIFICATION
----------	---

Product Identifier: Ultrapac Renovate
SDS Number: A217
Revision Date: June 15, 2018
Version: 46-58A

Manufacturer: **Canadian Contact:**

Legend Brands
 325 S. Price Rd.
 Chandler, AZ 85224
 Phone: 480-899-7000
 Fax: 480-786-9538
 Email: sds@legendbrands.com
www.legendbrandscleaning.com

Legend Brands
 4520 Eastgate Parkway
 Mississauga, ON L4W 3W6
 Phone: 800-932-3030

Emergency Information: INFOTRAC 1-800-535-5053 International 1-352-323-3500

2	HAZARDS IDENTIFICATION
----------	-------------------------------

Classification of Substance

GHS Classification in Accordance with 29 CFR 1910 (OSHA HCS):

- Health, Acute toxicity, 5 Oral
- Health, Acute toxicity, 4 Dermal
- Health, Serious Eye Damage/Eye Irritation, 2 A

GHS Label Elements, Including Precautionary Statements

GHS Signal Word: **WARNING**

GHS Hazard Pictograms:



GHS Hazard Statements:

- H303 - May be harmful if swallowed
- H312 - Harmful in contact with skin
- H319 - Causes serious eye irritation

GHS Precautionary Statements:

- P264 - Wash thoroughly after handling.
- P280 - Wear protective gloves/protective clothing/eye protection/face protection.
- P302+352 - IF ON SKIN: Wash with soap and water.
- P305+351+338 - IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing.
- P312 - Call a POISON CENTER or doctor/physician if you feel unwell.
- P337+313 - If eye irritation persists: Get medical advice/attention.
- P363 - Wash contaminated clothing before reuse.

Route of Entry: Eyes; Skin; Inhalation;
Target Organs: Eyes; Skin;
Inhalation: Minimal respiratory tract irritation may occur with exposure to a large amount of material.
Skin Contact: Causes irritation.
Eye Contact: Irritating to eyes; eye damage may occur.
Ingestion: Ingestion is not applicable route of entry for intended use.

3

COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Ingredients		
CAS#	%	Chemical Name
1310-58-3	2%	Potassium hydroxide, solution
102-71-6	1%	Triethanolamine

OSHA Regulatory Status:

This SDS contains valuable information critical to the safe handling and proper use of this product. This SDS should be retained and available for employees and other users of this product.

4

FIRST AID MEASURES

Inhalation:	If symptoms develop, move victim to fresh air; if symptoms persist, obtain medical attention.
Skin Contact:	Wash with soap and water. If irritation persists consult medical personnel.
Eye Contact:	Immediately flush eyes with large amounts of water for at least 15 minutes, lifting eyelids occasionally to facilitate irrigation. Get immediate medical attention.
Ingestion:	If swallowed, DO NOT induce vomiting unless directed to do so by medical personnel. If injured party is conscious, give two glasses of water. Seek medical attention.

5

FIRE FIGHTING MEASURES

Flash Point:	100°C/ 212°F
Flash Point Method:	Closed Cup

Wear self-contained breathing apparatus and other protective clothing. Use any standard agent - choose the one most appropriate for type of surrounding fire.

6

ACCIDENTAL RELEASE MEASURES

Keep away from drains and ground water. Keep all unnecessary personnel away. Spill area may be slippery. Pick up excess with inert absorbent material and place into separate waste container. Ventilate area and wash spill site after material pickup is complete. Consult an expert on disposal of recovered material and ensure conformity to local disposal regulations.

7

HANDLING AND STORAGE

Handling Precautions:	Avoid contact with eyes, skin, or clothing; Consider normal working hygiene. Handle with care and avoid spillage on the floor (slippage). Keep away from sources of ignition; wash thoroughly after handling.
Storage Requirements:	Keep away from children. Store in cool/dry area; Keep container closed.

8

EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering Controls:	Normal room ventilation is satisfactory for limited use.
Personal Protective Equipment:	HMIS PP, B Safety glasses, Gloves

No OSHA PEL established for listed chemicals

9

PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	Opaque Yellow
Physical State:	Liquid
Odor:	Citrus
Solubility:	Soluble
Specific Gravity or Density:	9.80 lb/gal
Potentia Hydrogenii:	12.98 as is / 10.5 - 11.5 RTU

10	STABILITY AND REACTIVITY
-----------	---------------------------------

Chemical Stability: Product is stable under normal conditions.
Conditions to Avoid Identification: None known
Materials to Avoid Identification: None known
Hazardous Decomposition: Exposure to fire may liberate carbon dioxide, carbon monoxide, organic acids, and other unidentified thermal decomposition products from this product or its packaging.
Hazardous Polymerization: Will not occur.

11	TOXICOLOGICAL INFORMATION
-----------	----------------------------------

Toxicity Data:

Potassium hydroxide 1310-58-3

Oral (LD 50): 273 mg/kg - Rat

Inhalation (LC): Not listed on RTECS

Skin irritation: Severe - Human

Eye irritation: Severe - Rabbit

Sensitization: Not considered an occupational sensitizer

Triethanolamine 102-71-6

Oral (LD 50): 4920 mg/kg - Rat

Inhalation (LC): Not listed on RTECS

Skin irritation: Mild - Human

Eye irritation: Severe - Rabbit

Sensitization: Not considered an occupational sensitizer

12	ECOLOGICAL INFORMATION
-----------	-------------------------------

On the basis of available information, this material is not expected to produce any significant environmental effects when recommended use instructions are followed.

13	DISPOSAL CONSIDERATIONS
-----------	--------------------------------

Recommendation: Consult with the disposal agency and the relevant authorities. Empty containers may be cleaned with water.

14	TRANSPORT INFORMATION
-----------	------------------------------

Limited Quantity (Ltd Qty) Ship in accordance with 49 CFR parts 100-185.

15	REGULATORY INFORMATION
-----------	-------------------------------

COMPONENT / (CAS/PERC) / CODES

*Potassium hydroxide, solution (1310583 2%) CERCLA, CSWHS, MASS, OSHAWAC, PA, TSCA, TXAIR, WHMIS

*Triethanolamine (102716 1%) HAP, MASS, PA, TSCA, TXAIR

REGULATORY KEY DESCRIPTIONS

All components are listed on TSCA

CERCLA = Superfund clean up substance
 CSWHS = Clean water Act Hazardous substances
 HAP = Hazardous Air Pollutants
 MASS = MA Massachusetts Hazardous Substances List
 OSHAWAC = OSHA Workplace Air Contaminants
 PA = PA Right-To-Know List of Hazardous Substances
 TXAIR = TX Air Contaminants with Health Effects Screening Level
 WHMIS = workplace Haz Mat Info Sys Canada



CALIFORNIA PROPOSITION 65 CARCINOGENS

Warning: The following ingredients present in the product are known to the state of California to cause cancer.

<u>Chemical Name</u>	<u>CAS-No.</u>
Diethanolamine	111-42-2

16	OTHER INFORMATION
-----------	--------------------------

NFPA: Health = 2, Fire = 1, Reactivity = 0, Specific Hazard = n/a
HMIS III: Health = 2, Fire = 1, Physical Hazard = 0
HMIS PPE: B - Safety Glasses, Gloves



This document is prepared in accordance with 29 CFR 1910.1200. The purpose of this section is to ensure that the hazards of all chemicals produced or imported are evaluated, and that information concerning their hazards is transmitted to employers and employees.

All information appearing herein is based upon data obtained from the raw material manufacturer and/or recognized technical sources. While the information above is believed to be true and accurate, the author makes no representations as to its accuracy or sufficiency. Conditions of use are beyond the manufacturer's control; therefore the users are responsible to verify this data under their own particular conditions, applications and regulations to determine if the product is suitable for their particular purposes. The users assume all risks of product use, handling, disposal, reliance upon, publication or use of the information contained herein. This information applies only to the product designated above and does not necessarily apply to its use in combination with other materials, products, chemical compounds, structures or processes.

Prepared by: EHS Manager Phone Number: [480] 899-7000